

Benzene CAS No 71-43-2

MATERIAL SAFETY DATA SHEET SDS/MSDS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifiers

Product name : Benzene

CAS-No. : 71-43-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Industrial & for professional use only.

1.3 Details of the supplier of the safety data sheet

> Company : Pallav Chemicals & Solvents Pvt. Ltd

253, Shiv Shakti Industrial Estate, Opp Mittal Estate Andheri Kurla Road, Andheri (E), Mumbai - 400050

INDIA

Telephone : +91 22 4928 4000

Email sales@pallavchemicals.com

1.4 Emergency telephone number

+91 22 4928 4000 (9:00am - 6:00 pm) [Office

Emergency Phone # hoursl

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315

Eye irritation (Category 2), H319

Germ cell mutagenicity (Category 1B), H340

Carcinogenicity (Category 1A), H350

Specific target organ toxicity - repeated exposure (Category 1), H372

Aspiration hazard (Category 1), H304

Chronic aquatic toxicity (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H340 May cause genetic defects.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P273 Avoid release to the environment.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/

physician.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

Supplemental Hazard none

Statements

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : 6H6

Molecular weight : 78,11 g/mol

CAS-No. : 71-43-2

EC-No. : 200-753-7

Index-No. : 601-020-00-8

Registration number : 01-2119447106-44-XXXX

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component Classification Concentration

Benzene

CAS-No. 71-43-2 Flam. Liq. 2; Skin Irrit. 2; Eye <= 100 %

EC-No. 200-753-7 Irrit. 2; Muta. 1B; Carc. 1A; Index-No. 601-020-00-8 STOT RE 1; Asp. Tox. 1; Registration number 01-2119447106-44-XXXX Aquatic Chronic 3; H225, H315, H319, H340, H350,

11070, 11010, 11040,

H372, H304, H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment

needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or

mixture Carbon oxides

Flash back possible over considerable distance., Container explosion may occur under fire conditions.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Avoid exposure - obtain special instructions before use.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Colour: clear, colourless

b) Odourc) Odour Thresholdd) pHNo data availableNo data available

e) Melting point/freezing Melting point/range: 5,5 °C - lit.

point

f) Initial boiling point and 80 °C - lit.

boiling range

g) Flash point -10,99 °C - closed cup

h) Evaporation rate No data availablei) Flammability (solid, gas) No data available

j) Upper/lower Upper explosion limit: 8 %(V) flammability or Lower explosion limit: 1,3 %(V)

explosive limits

k) Vapour pressure 221,3 hPa at 37,7 °C

99,5 hPa at 20,0 °C

l) Vapour density No data available

m) Relative density 0,874 g/cm3 at 25 °C

n) Water solubility ca.1,88 g/l at 23,5 °C - soluble

o) Partition coefficient: n-

octanol/water

log Pow: 2,13 at 25 °C

p) Auto-ignition 562,0 °C

temperature

q) Decomposition No data available

temperature

r) Viscosity No data available
 s) Explosive properties No data available
 t) Oxidizing properties No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

acids, Bases, Halogens, Strong oxidizing agents, Metallic salts

10.6 Hazardous decomposition products

Other decomposition products - No data available In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - > 5.960 mg/kg (OECD Test Guideline 401)

LC50 Inhalation - Rat - female - 4 h - 43,7 mg/l (OECD Test Guideline 403)

LD50 Dermal - Rabbit - 8.263 mg/kg

Skin corrosion/irritation

Skin - Rabbit

Result: Skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit Result: Eye irritation

Respiratory or skin sensitisation

Maximisation Test (GPMT) - Guinea pig Result: Does not cause skin sensitisation.

Germ cell mutagenicity

Laboratory experiments have shown mutagenic effects.

In vivo tests showed mutagenic effects

Chinese hamster lung cells

Result: positive

OECD Test Guideline 475

Mouse - male Result: positive

Carcinogenicity

Carcinogenicity - Human - male - Inhalation

Tumorigenic:Carcinogenic by RTECS criteria. Leukaemia Blood:Thrombocytopenia.

Carcinogenicity - Rat - Oral

Tumorigenic:Carcinogenic by RTECS criteria. Endocrine:Tumors. Leukaemia

This is or contains a component that has been reported to be carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

Human carcinogen.

IARC: 1 - Group 1: Carcinogenic to humans (Benzene)

Reproductive toxicity

Reproductive toxicity - Mouse - Intraperitoneal

Effects on Fertility: Pre-implantation mortality (e.g., reduction in number of implants per female; total number of implants per corpora lutea). Effects on Embryo or Fetus: Fetal death.

Developmental Toxicity - Rat - Inhalation

Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord). Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Developmental Toxicity - Mouse - Inhalation

Effects on Embryo or Fetus: Cytological changes (including somatic cell genetic material). Specific Developmental Abnormalities: Blood and lymphatic system (including spleen and marrow).

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

May be fatal if swallowed and enters airways.

Additional Information

Repeated dose Rat - male and female - Oral - NOAEL: 100 mg/kg - OECD Test Guideline 408

toxicity

RTECS: CY1400000

Nausea, Dizziness, Headache, narcosis, Inhalation of high concentrations of benzene may have an initial stimulatory effect on the central nervous system characterized by exhilaration, nervous excitation and/or giddiness, depression, drowsiness, or fatigue.

The victim may experience tightness in the chest,

breathlessness, and loss of consciousness. Tremors, convulsions, and death due to respiratory paralysis or circulatory collapse can occur in a few minutes to several hours following severe exposures. Aspiration of small amounts of liquid immediately causes pulmonary edema and hemorrhage of pulmonary tissue. Direct skin contact may cause erythema. Repeated or prolonged skin contact may result in drying, scaling dermatitis, or development of secondary skin infections. The chief target organ is the hematopoietic system. Bleeding from the nose, gums, or mucous membranes and the development of purpuric spots, pancytopenia, leukopenia, thrombocytopenia, aplastic anemia, and leukemia may occur as the condition progresses. The bone marrow may appear normal, aplastic or hyperplastic, and may not correlate with peripheral blood-forming tissues. The onset of effects of prolonged benzene exposure may be delayed for many months or years after the actual exposure has ceased., Blood disorders

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 15,00 - 32,00 mg/l - 96 h

Toxicity to daphnia and EC50 - Ceriodaphnia dubia (water flea) - 17,2 mg/l - 48 h

other aquatic invertebrates

Toxicity to algae Growth inhibition EC50 - Pseudokirchneriella subcapitata (green algae) - 100

ma/l - 72 h

(OECD Test Guideline 201)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 96 % - Readily biodegradable

(OECD Test Guideline 301F)

12.3 Bioaccumulative potential

Bioaccumulation Leuciscus idus (Golden orfe) - 3 d

- 0,05 mg/l

Bioconcentration factor (BCF): 10

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1114 IMDG: 1114 IATA: 1114

14.2 UN proper shipping name

ADR/RID: BENZENE IMDG: BENZENE IATA: Benzene

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 453/2010.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Benzene CAS-No.: 71-43-2

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Carcinogens: category 1A Restricted to professional users.

See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

Benzene CAS-No.: 71-43-2

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous

substances, preparations and articles (Annex XVII)

Shall not be placed on the market, or used, as a substance or in mixtures See

Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

Benzene CAS-No.: 71-43-2

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous

substances, preparations and articles (Annex XVII)

Not permitted in toys or part of toys

See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

Benzene CAS-No.: 71-43-2

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export

and import of dangerous chemicals

ANNEX I, PART 1: List of chemicals subject to export notification procedure

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Pallav Chemicals & Solvents Pvt. Ltd and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.pallavchemicals.com for additional terms and conditions of sale.