

# Ethyl Acetate CAS No 141-78-6

# MATERIAL SAFETY DATA SHEET SDS/MSDS

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Ethyl Acetate

CAS-No. : 141-78-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Industrial & for professional use only.

1.3 Details of the supplier of the safety data sheet

Company : Pallav Chemicals & Solvents Pvt. Ltd

253, Shiv Shakti Industrial Estate, Opp Mittal Estate Andheri Kurla Road, Andheri (E), Mumbai - 400050

**INDIA** 

Telephone : +91 22 4928 4000

Email : sales@pallavchemicals.com

1.4 Emergency telephone number

+91 22 4928 4000 (9:00am - 6:00 pm) [Office

Emergency Phone # : hours]

#### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No

1272/2008 Flammable liquids (Category 2), H225

Eye irritation (Category 2), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 For the full text of the H-Statements mentioned in this Section, see Section 16.

## Classification according to EU Directives 67/548/EEC or 1999/45/EC

F Highly flammable R11 Xi Irritant R36 R66 R67

For the full text of the R-phrases mentioned in this Section, see Section 16.

## 2.2 Label elements

# Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P261 Avoid breathing vapours.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.1Substances

Formula : 4H8O2
Molecular weight : 88,11 g/mol
CAS-No. : 141-78-6
EC-No. : 205-500-4
Index-No. : 607-022-00-5

Registration number : 01-2119475103-46-XXXX

## Hazardous ingredients according to Regulation (EC) No 1272/2008

Component Classification Concentration

Ethyl acetate

CAS-No. 141-78-6 Flam. Liq. 2; Eye Irrit. 2; STOT <= 100 %

EC-No. 205-500-4 SE 3; H225, H319, H336,

Index-No. 607-022-00-5 EUH066

Registration number 01-2119475103-46-XXXX

## Hazardous ingredients according to Directive 1999/45/EC

Component Classification Concentration

Ethyl acetate

CAS-No. 141-78-6 F, Xi, R11 - R36 - R66 - R67 <= 100 %

EC-No. 205-500-4 Index-No. 607-022-00-5

Registration number 01-2119475103-46-XXXX

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment

needed No data available

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### 5.2 Special hazards arising from the substance or

mixture No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

# 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

## 6.4 Reference to other sections

For disposal see section 13.

# **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): Flammable liquids

# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

## Components with workplace control parameters

## **Derived No Effect Level (DNEL)**

Application Area	Exposure routes	Health effect	Value
Workers Workers Workers Workers Consumers	Inhalation Inhalation Skin contact Inhalation Inhalation Inhalation	Acute systemic effects Acute local effects Long-term systemic effects Long-term systemic effects Long-term local effects Acute local effects, Acute systemic	1468 mg/m3 1468 mg/m3 63mg/kg BW/d 734 mg/m3 734 mg/m3
Consumers Consumers Consumers Consumers	Skin contact Inhalation Ingestion Inhalation	effects Long-term systemic effects Long-term systemic effects Long-term systemic effects Long-term local effects	37mg/kg BW/d 367 mg/m3 4,5mg/kg BW/d 367 mg/m3

#### **Predicted No Effect Concentration (PNEC)**

Compartment	Value
Soil	0,24 mg/kg
Marine water	0,026 mg/l
Fresh water	0,26 mg/l
Marine sediment	0,125 mg/kg
Fresh water sediment	1,25 mg/kg

#### 8.2 Exposure controls

## Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

## Personal protective equipment

## Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

## **Body Protection**

impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

## Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

a) Appearance Form: clear, liquid

Colour: colourless

b) Odour No data available

c) Odour Threshold No data available

d) pH No data available

e) Melting point/range: -84 °C

point/freezing point

f) Initial boiling point 76,5 - 77,5 °C

and boiling range

g) Flash point -2,99 °C - closed cup

h) Evaporation rate No data available

i) Flammability (solid, gas) May form explosive dust-air mixture.

j) Upper/lower Upper explosion limit: 11,5 %(V) flammability or Lower explosion limit: 2,2 %(V)

explosive limits

k) Vapour pressure 97,3 hPa at 20,0 °C
 l) Vapour density No data available
 m) Relative density 0,90 g/cm3 at 20 °C

n) Water solubility soluble

o) Partition coefficient: n- log Pow: 0,73

octanol/water

p) Auto-ignition 427,0 °C

temperature

q) Decomposition No data available

temperature

r) Viscosity No data availables) Explosive properties No data available

t) Oxidizing properties No data available

#### 9.2 Other safety information

Surface tension 24,0 mN/m at 20,0 °C

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No data available

# 10.2 Chemical stability

Stable under recommended storage conditions.

## 10.3 Possibility of hazardous reactions

No data available

# 10.4 Conditions to avoid

Heat, flames and sparks.

#### 10.5 Incompatible materials

Strong oxidizing agents

#### 10.6 Hazardous decomposition products

Other decomposition products - No data available In the event of fire: see section 5

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

#### **Acute toxicity**

LD50 Oral - Rat - 5.620 mg/kg

LC50 Inhalation - Mouse - 2 h - 45.000 mg/m3

LD50 Dermal - Rabbit - > 18.000 mg/kg

#### Skin corrosion/irritation

Skin - Rabbit

Result: Mild skin irritation (OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

#### Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified

as probable, possible or confirmed human carcinogen by IARC.

## Reproductive toxicity

No data available

## Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

## Specific target organ toxicity - repeated exposure

No data available

# **Aspiration hazard**

No data available

#### **Additional Information**

RTECS: AH5425000

Inhalation of high concentrations may cause:, Headache, Drowsiness, Dizziness, Vomiting, narcosis, anemia, Central nervous system depression

Kidney - Irregularities - Based on Human Evidence

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 350,00 - 600,00 mg/l - 96 h

LC50 - Pimephales promelas (fathead minnow) - 220,00 - 250,00 mg/l - 96 h

Toxicity to daphnia and

other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 2.300,00 - 3.090,00 mg/l - 24 h

LC50 - Daphnia magna (Water flea) - 560 mg/l - 48 h

Toxicity to algae EC50 - Algae - 4.300,00 mg/l - 24 h

EC50 - SELENASTRUM - 1.800,00 - 3.200,00 mg/l - 72 h

# 12.2 Persistence and degradability

Biodegradability Result: 79 % - Readily biodegradable

(OECD Test Guideline 301D)

#### 12.3 Bioaccumulative potential

Bioaccumulation - 3 d

Bioconcentration factor (BCF): 30

## 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Other adverse effects

No data available

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

## Contaminated packaging

Dispose of as unused product.

# **SECTION 14: Transport information**

#### 14.1 UN number

ADR/RID: 1173 IMDG: 1173 IATA: 1173

# 14.2 UN proper shipping name

ADR/RID: ETHYL ACETATE IMDG: ETHYL ACETATE Ethyl acetate

## 14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

## 14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

#### 14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

#### 14.6 Special precautions for user

No data available

# **SECTION 15: Regulatory information**

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No data available

## 15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

#### **SECTION 16: Other information**

## Full text of H-Statements referred to under sections 2 and 3.

EUH066 Repeated exposure may cause skin dryness or cracking.

Eye Irrit. Eye irritation Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

STOT SE Specific target organ toxicity - single exposure

## Full text of R-phrases referred to under sections 2 and 3

F Highly flammable

Xi Irritant

R11 Highly flammable. R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

#### **Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Pallav Chemicals & Solvents Pvt. Ltd and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.pallavchemicals.com for additional terms and conditions of sale.